



www.atpkg.com



# HP100

## GENERAL PURPOSE GRADE HOT MELT PACKAGING TAPE

### TYPICAL APPLICATIONS:

- For manual or automated industrial carton sealing of lightweight cartons with minimal exposure to handling, shipping and load stress

### PRODUCT FEATURES:

- Instant, permanent bond to a wide range of substrates and surfaces
- Special release coating for consistent, low force unwind off the roll
- Performs reliably to the core for efficient tape consumption
- High-tack adhesive for a long-lasting, secure seal

### STANDARD WIDTHS:

- 48, 72 mm

### STANDARD LENGTHS:

- Hand grade: 132 m
- Machine grade: 914, 1828 m

### PHYSICAL PROPERTIES

Tensile Strength  
Adhesion to Stainless Steel  
Thickness  
Elongation  
Holding Power to Fiberboard  
Application Temperature Range  
Service Temperature Range

### IMPERIAL

21 lbs/in width  
43 oz/in width  
1.6 mils  
150%  
10,000+ minutes  
35 F to 110 F  
-20 F to 180 F

### METRIC

36.8 N/10 mm  
4.71 N/10 mm  
0.041 mm  
150%  
10,000+ minutes  
2 C to 43 C  
-29 C to 82 C

