



www.atpkg.com



AT PACKAGING

SALES  SERVICE



PET STRAPPING

Polyester strapping smooth and embossed, available width 9 - 32 mm (3/8" - 1 1/4"), for extremely challenging types of use that require increased edge and welding joint strength; TYCOON® is suited for applications that require high strap tension and where there exists an elevated risk of shock splitting (e.g., wood and timber industry). Furthermore, it is suitable for sharp-edged products encountered in the metal or building supplies industries. Consequently, it guarantees trouble-free manufacturing processes on fully automatic strapping machines.

XTended Tenacity – enhanced tenacity

- increased edge strength
- free from shock splitting – improved characteristics with regard to shock splitting, even at low ambient temperatures

XTended Shock Reserve – increased shock reserve

- this strapping is capable of absorbing even extremely high shock loads
- ideal combination of high breaking strength and 16% elongation

XTended weldability – increased welding joint strength

- higher welding joint strength, even at low ambient temperatures

TYCOON® XTend – better performance with identical dimensions!

Upgraded manufacturing technology, an improved raw material process, and, most of all, a new formula including a patented additive form the basis for the new generation of

TYCOON® XTend strapping products. A leap in performance in our new green.

TYCOON® XTend – also available in jumbo make-up!

Our XTend polyester strapping is available in different jumbo versions and offers you significantly more meters per coil. Not only does this reduce the number of required coil changes, but it also enhances the cost-effectiveness of your application.

AAR certification

Also, our XTend polyester strapping has been certified and approved by the AAR (Association of American Railroads) for open top rail transport (Open Top Loading Rules). In the NAFTA zone, securing cargo on railroad wagons by means of strapping is permitted only with this special printed and highly tear resistant strapping. AAR marking is applied on the strapping by using our HQ Inkjet printing process.