



www.atpkg.com



# SB-2EX RANDOM

SB-2EX Random allows users to run a variety of case sizes without having to manually adjust for each box. The system automatically adjusts the side rails and tape head height for different size cases.

## MAIN FEATURES:

- Box depth memory function
- Plug-in and go operation
- Accommodates wide box sizes
- Industrial strength side belts
- Interchangeable top and bottom tape cartridges
- Adjustable leg extensions
- Casters for transportation within plant
- Emergency stop button
- Reset button
- Powder coated 12 gauge steel
- Low maintenance

## OPTIONS:

- 3" Tape Head
- Safety Enclosure
- Front And Rear Packing Table

## TAPING SPECIFICATIONS:

- Sealer Type: Random side belt, top and bottom case sealer
- Machinery Makeup: Industrial strength 12 gauge steel, powder coated for durability
- Belt Speed: 75 fpm
- Tape Speed: 15-20 cases per min., depending on box size and operator efficiency
- Conveyor Height Adj.: 21.2" to 34.6"
- Tape Size 2" wide pressure sensitive tape, up to 15" diameter rolls, optional 3" wide tape
- Tape Cartridge Proven design requires no lubrication, designed for simple tape threading, removable for maintenance and interchangeable with top or bottom cartridges
- Drive Motor Two (2) drive motors
- Electrical Requirements 110 VAC, 60Hz, 4.0A
- Air Requirements 80 PSI
- Agency Approvals CE Certification