



www.atpkg.com



SB/TB-2

SIDE BELT & TOP BELT CASE TAPER

The SB/TB-2 Case Taper offers the quality that you have come to rely on from Eastey. The system's unique and simple design has proven to be one of the most reliable case tapers on the market today, keeping production and maintenance efforts to a minimum and providing fast and efficient alternatives to hand taping.

STANDARD FEATURES:

- Plug-in and go operation
- Fast and easy box size changes
- Industrial strength side belts
- Interchangeable top and bottom tape cartridges
- Emergency stop button
- Adjustable leg extensions
- Casters included for transportation within plant
- Front and rear pack tables included to allow for case packing
- Top squeezers push top flaps together on overfilled cases
- Powder coated 12 gauge steel
- Low maintenance, no air required

OPTIONS:

- 3" Tape Head

TAPING SPECIFICATIONS:

- Sealer Type: Side and top belt case sealer
- Machinery Makeup: Industrial strength 12 gauge steel, powdered coated for durability
- Belt Speed: 75 fpm
- Tape Speed: 30 cases per min., depending on box size and operator efficiency
- Height Adjustment: Standard adjustable legs for 26.8" to 34.6" conveyor heights
- Tape Size: 2" wide pressure sensitive tape, up to 15" diameter rolls, optional 3" wide tape
- Tape Cartridge: Proven design requires no lubrication, designed for simple tape threading, removable for maintenance and interchangeable with top or bottom cartridges
- Drive Motor: Three (3) 1/4 HP drive motors
- Electrical Requirements: 110 VAC, 60Hz, 4.0A
- Agency Approvals: CE Certification

BOX SPECIFICATIONS:

Min Box Size - (Length) 4.75" (Width) 7" (Depth) 4.7"

Min Box Size - (Length) Infinite (Width) 27.5" (Depth) 27.5"

DIMENSIONS:

