



www.atpkg.com



AT PACKAGING
SALES  SERVICE



H. \ W.	550	650	850	1050	1250	1650	1850
400	✓	✗	✓	✗	✗	✗	✗
500	✗	✓	✓	✓	✓	✓	✗
600	✗	✗	✓	✗	✗	✗	✗
800	✗	✗	✓	✓	✓	✗	✓
1000	✗	✗	✗	✓	✓	✗	✗

✓ Standard Size (mm) ✓ Available Arch Size ✗ Not available

TP-702

The equipment TP-702 with 650mm (25- 1/2”) x 500mm (19- 2/3”) arch is an innovative world-class high-speed automatic strapping machine. It comes equipped with all industry’s standard features and several creative user-friendly designs. Mercury TP-702 offers the most optimal performance, highest speed, easiest maintenance and the most cost-effective solution in its class Today. It is suitable for 5mm (13/64”) to 9mm (3/8”) strap.

STANDARD FEATURES:

- Robust & Compact Mechanical Strapping Head
- Free Access to Strap Guides (patents registered)
- Waist-High Auto Strap Feeding
- Waist-High Quick Coil Change (patents registered)
- Ergonomic Cycle Initiation
- Turnable Operating Control Panel
- Front Foot-Bar Switch
- Auto Strap Ejector
- Adjustable Table Height
- Up to 65 cycles per minute
- Maximum tension 45 kg

OPTIONS:

- Photo-Eye Switch
- Rear Foot Bar Switch

DIMENSIONS (MM):

