



**ZP28** 

## PNEUMATIC STRAPPING TOOL WITH VIBRATION SEALING

## **FEATURES:**

- Powerful tension, Maxi.350Kgs (3500N) for heavy duty plastic strapping jobs.
- Automatic tension, friction-weld and cut, no metal seals required.
- Air pressure manometer for on-site air supply monitoring.
- Adjustable tension force & sealing time for various strap specifications.
- Much smaller air hose at 1/4" I.D. for flexible operation without hose tangling.
- Alloyed Magnesium Aluminum mechanism ensures light weight and durable structure.
- Patented single motor structure reduces weight and lower maintenance cost.
- Modularized structure and reliable mechanism for easy and low-cost maintenance.
- Ergonomic design and excellent weight distribution to reduce hand fatigue
- Built-in safety device for tension setting and prevent from scratching or breaking the strap.
- Easy "One-Step" straps inserting.
- User self-adjustable front & rear strap width guiders to assure perfect strap alignment.
- User changeable strap cutting blade and other wearing parts.
- Optional hanger to reduce operation fatigue.

Model	Air Pressure	Strapping	Strap Width		Strap Thickness		Tension Range		Sealing Efficiency
ZP28-9A	6~7 kg/cm <sup>2</sup>	PP & PET	16mm	5/8po	0.75-1.27mm	.02905po	20-180kg	44 -397 lbs	85 +-5%
	87~101.5psi		19mm	3/4po	0.65-1.27mm	.02605po	60-350kg	132 -772 lbs	